



SB 18 SUBWOOFER



Description	Compact subwoofer: 1 x 18" amplified by LA4X / LA8 / LA12X
Low frequency limit (-10 dB)	32 Hz ([SB18_100])
Maximum SPL¹	138 dB ([SB18_100])
Nominal directivity	Standard or cardioid configurations
Transducers	1 x 18" cone driver
Acoustical load	Bass-reflex, L-Vents
Nominal impedance	8 Ω
Connectors	IN: 1 x 4-point speakON LINK: 1 x 4-point speakON
Rigging and handling	Flush-fitting four-point rigging system 1 x 35 mm pole mount socket 4 handles, 8 protective corner stops
Weight (net)	52 kg / 115 lb
Cabinet	Premium grade Baltic beech and birch plywood
Front	Coated steel grill Acoustically neutral 3D fabric
Rigging components	High grade steel with anti-corrosion coating
Finish	Dark grey brown Pantone 426 C
IP	IP55


¹ Peak level at 1 m under half space conditions using pink noise with crest factor 4 (preset specified in brackets).

ISOCONTOUR




► SPL mapping of a block of four SB 18 in standard (left) and cardioid (right) arrangements, using surfaces of equal sound pressure with three dB step colored scale.


DIMENSIONS



Front



Side



Top